

Bollard 200

SPECIFICATIONS

CONTROL UNIT -	900CT-D100
POWER SUPPLY -	240 VOLT AC
MOTOR POWER -	240 VOLT AC
PROTECTION -	IP67
RATED ABSORBED POWER -	130 WATTS
MOTOR ABSORPTION -	1.4 AMPS
BATTERY BACK UP OPTION -	NO
SOLAR POWER OPTION -	NO
OPENING TIME -	9 SECONDS
BOLLARD DIMENSIONS -	194MM X 700MM
CYCLES PER DAY -	500
RUNNING TEMPERATURE -	-20 TO +60 DEGREES
BASE DIMENSIONS -	1180H X 360W X 360D
WEIGHT -	105 KG

Bollard 200 is the largest of our electro mechanical rising bollard range and second in size only to the hydraulic Bull. It rises to 700mm in height in only nine seconds and comes complete with flashing LED top ring lights for high visibility and safety at night.



Automatic rising bollards have many uses but when you look at where they fit in the road barrier range two things are obvious, firstly they are the highest in security of the group and secondly they are pedestrian friendly when compared to the other options. You can connect up to four rising bollard 200 to a single logic control giving the ability to space four bollards as close as 1200mm and still provide a total opening of 7200mm giving easy and safe access to authorised vehicles such as public buses to pedestrian areas. They also make an ideal access control situation for high security buildings keeping all but authorised vehicles from approaching the building or parking at the perimeter. Bollard 200 is completely self contained making installation and maintenance simpler and more cost efficient as well as being suitable for retro fit installations.



<http://www.road-barriers.com.au>